August 7, 2008

Atty Docket No.: NL031256 (79002-45)

Serial No.: 10/577,112 Filed: April 25, 2006

Page 3 of 8

**CLAIM LISTING** 

A listing of an entire set of claims 1-8 is submitted herewith per 37 C.F.R. §1.121. This

listing of claims 1-8 will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A lamp comprising a burner (1) and a cap (2) to connect the lamp

with a lampholder, whereby [[the]] <u>a</u> shape of the cap (2) determines [[the]] <u>a</u> type of lampholder

to which the lamp can be connected, characterized in that said shape of the cap (2) is established

after the burner (1) and the cap (2) of the lamp are assembled by a creation of at least one recess

(9) in the cap (2) which permits insertion of at least the burner (1) in the lampholder.

2. (Currently Amended) A lamp as claimed in claim 1, characterized in that said shape of

the cap (2) is established by breaking away[[, or not, a]] at least one break away part (8) provided

at the cap (2) to create the at least one recess (9) in the cap (2).

3. (Previously Presented) A lamp as claimed in claim 1, characterized in that the cap (2)

comprises a row of break away parts (8), whereby one or more break away parts (8) may be

removed.

4. (Currently Amended) A lamp as claimed in claim [[1]] 2, characterized in that two break

away parts (8) are removed, whereby two separate recesses are created (9).

5. (Currently Amended) A lamp as claimed in claim [[1]] 2, characterized in that the at

<u>least one</u> break away [[parts (8) are]] <u>part (8) is</u> present in a radially extending flange (3) of the

cap (2).

6. (Currently Amended) A method for manufacturing a lamp comprising a burner (1) and a

cap (2) to connect the lamp with a lampholder, whereby [[the]] a shape of the cap (2) determines

[[the]] a type of lampholder to which the lamp can be connected, characterized in that the shape

August 7, 2008

Atty Docket No.: NL031256 (79002-45)

Serial No.: 10/577,112 Filed: April 25, 2006

Page 4 of 8

of the cap (2) is established after the burner (1) and the cap (2) are assembled to form the lamp by a creation of at least one recess (9) in the cap (2) which permits insertion of at least the burner (1) in the lampholder.

- 7. (Currently Amended) A method as claimed in claim 6, characterized in that said shape of the cap (2) is established by breaking away a <u>break away</u> part (8) of the cap (2), whereby [[that]] the <u>break away</u> part (8) was connected to [[the]] a reminder of the cap (2) [[by a relative weak connection]].
- 8. (Currently Amended) A method as claimed in claim 6, characterized in that said shape of the cap (2) to be established depends on [[the]] results of a testing procedure of the lamp.